

因为专注 所以信赖
BECAUSE THE FOCUS SO TRUST



金世纪(江苏)智能科技有限公司
GolCentury(Jiangsu) Intelligent Technology Co., Ltd.

金世纪(洛阳)车轮制造有限公司
Golden Century(LUOYANG) WHEEL MANUFACTURING CO., LTD.

联系电话: 0514-80806060 0514-80806057
0514-80806058 13083591936

传真: 0514-80806067
网址: gb.jsj-wheel.cn
邮箱: jsj-wheel@jsj-wheel.com

地址: 扬州市江都区仙城工业园航天路10号

900280 股票代码

韩交所上市



金世纪集团
Golden Century Group



金世纪(江苏)智能科技有限公司
GolCentury(Jiangsu) Intelligent Technology Co., Ltd.

金世纪(洛阳)车轮制造有限公司
Golden Century(LUOYANG) WHEEL MANUFACTURING CO., LTD.

企业简介 Enterprise Profile

金世纪(江苏)智能科技有限公司(Golden Century(Jiangsu) Intelligent Technology Co., Ltd. 是一家香港全资控股企业位于古城扬州东郊,环境优美,交通便利,紧邻京沪、宁通高速。本公司专业生产拖拉机钢圈、大、中型和特大型拖拉机钢圈,汽车、工程车辆钢圈。本公司具备为用户设计开发各类大型、特大型钢圈,目前是国内能生产最宽、直径最大的钢圈厂家,品种齐全。

公司在99年12月通过了ISO9002国际质量体系认证。我们是中国农业机械工业协会拖拉机分会的会员单位,同时公司通过IATF16949:2016国际汽车质量体系认证。其“江威牌”钢圈在业内具有极高的知名度,公司连续多年被评为“优秀供应商”。

我公司产品规格齐全,且畅销全国各地,部分产品外销美国、中东、澳大利亚、马来西亚等国。

为了解决公司产能日益供不应求的状况及公司未来发展需要,我公司于2011年在洛阳投资新建分公司,金世纪洛阳车轮制造有限公司并于2013年正式投产,极大的扩充了我公司的供货能力。

我公司总占地面积约80,000平方米,职工约400人,其中各类专业人才约60多人,我公司设备先进,技术力量雄厚。

企业始终贯彻以“质量第一、精益求精、用户至上”为目标,产品多年来赢得全国配套厂家的一致好评。



Golden Century (Jiangsu) Intelligent Technology Co., Ltd is a Hong Kong wholly-owned holding company which located in the eastern suburbs of Yangzhou City. Beautiful city with convenient transportation. Our company specializes in the production of medium and large tractor rims and steel rims for automobiles and engineering vehicles. The company design and development of various types of large, mega-large steel rims, can produce the largest tractor steel rims in China, the variety is complete.

The company passed ISO9002 International Quality System Certification in December 1999. We are a member of the tractor branch of China Agricultural Machinery Industry Association. In the meantime, the company has passed IATF16949:2016 International Automobile Quality System Certification. Its "Jiang Wei brand" steel rim in the industry has a very high reputation, the company for many years was named "Excellent supplier."

And our company product specification is complete, best-selling throughout the domestic market, some products exported to the United States, the Middle East, Australia, Malaysia and other countries.

In order to solve the company's production capacity is increasingly in short supply of the situation and the company's future development needs, our company in 2011 in Luoyang investment in new subsidiary, Dong Fang Hong(Luoyang) Wheel Manufacturing Co., Ltd. and in 2013 officially put into operation, greatly expanded the supply capacity of our company.

Our company covers an area of about 80,000 square meters, staff of about 400 people, including all kinds of professionals about 60 people, my company equipment is advanced, technical force is abundant.

Company have always implemented to "Quality first, excellent production, customer first" as the goal, products over the years to win the praise of customers throughout the country.





生产设备 Production Equipment

主要生产设备有车轮轮辋生产线8条, 阴极电泳生产线2条, 辐板生产线3条, 其中包括6000T压力机、1600T压力机、四米龙门刨床、大型阴极电泳线等精、大、稀设备。
We have 8 wheel rim production lines, 2 cathodic electrophoresis production lines and 3 radials production lines, in which including such precise, large and rare equipments/lines as 6000T press machine, 1600T press machine, 4M double housing planer and large cathodic electrophoresis production line.



质量控制 Quality Control

- 01、通过了GB/T 19001-2008/ISO9001:2008, 建立了完美的质量管理体系。
 - 02、公司拥有: 理化分析、机械性能实验、焊接探伤仪、盐雾试验机、三坐标检测等设备, 具备原材料进厂检测、焊接、涂装等特殊工艺验证能力。
 - 03、可依据GB/T 14785-2008进行车轮侧向负载疲劳和车轮扭转疲劳的型式实验。
01. Approved by GB/T19001-2008/ISO9001:2008 and a perfect quality control system has been established.
02. The company has such testing equipments that may conduct physical and chemical analysis and mechanical properties test as well as welding flaw director, salt spray test machine and three-coordinate measuring machine, owning the process verification capacity for raw material incoming inspection, welding and coating and other special processes.
03. The company may also conduct such type tests as wheel lateral load fatigue test and wheel torsional fatigue test in accordance with GB/T14785-2008.



荣誉 Honorary

多次被当地政府授予明星企业，重合同守信用企业等称号
被多个客户授予“优秀供应商”荣誉
连续多年被一拖评为“优秀供应商”



每一份荣誉，都见证着金世纪车轮昔日之辉煌，预示着未来之灿烂。
每一份荣誉，都凝聚着“金世纪人”的智慧和专业人士的认可。

成功上市

Successful listing



2016年10月19日,韩国KOSDAQ成功上市
股票代码: 900280



拖拉机系列 Tractor Series



车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
4.00Ex15	5.00-15	5	15	140	96	25	3.5	5
3.00Dx16	4.00-16	5	20	140	94	27	3.5	6
4.00Ex16	5.00-16	4	17	127	92.2	10	3.5	5
4.00Ex16	5.00-16	5	15	140	96	25	3.5	5
4.00Ex16	5.00-16	5	17	140	93	25	3.5	5
4.00Ex16	5.00-16	5	20	140	94	27	3.5	6
4.50Ex16	6.50-16	6	20	152	112	25	3.5	5
4.50Ex16	6.50-16	6	14	180	141	25	4	6
4.50Ex16	6.50-16	5	15	140	92	15	4	6
4.50Ex16	6.50-16	6	17	161	102	65	4	6
4.50Ex16	6.50-16	6	17	161	102	25	3.5	6
4.50Ex16	6.50-16	5	15	140	92	15	4	6
5.50Fx16	7.50-16	6	19	152	117.7	0	4	8
5.50Fx16	7.50-16	5	17.5	205	156	15	4	8
5.50Fx16	7.50-16	6	20	152.4	110	60	3.5	6
5.50Fx16	7.50-16	5	15	140	92	10	4	6
5.50Fx16	7.50-16	6	17	180	141	36	4	6
5.50Fx16	7.50-16	6	15	180	141	36	4	6
5.50Fx16	7.50-16	6	15	152.4	117.4	0	4	6
5.50Fx16	7.50-16	6	17	161	102	50	4	5
5.50Fx16	7.50-16	6	14.5	161	100.5	30	4	5
5.50Fx16	7.50-16	6	14	180	141	25	4	5
9.75x16.5	12.5-16.5	6	13	152.4	117.5	8	4	10
W9x18	11.2-18	6	17	161	102	136	4	8

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
5.50Fx20	7.50-20	6	19	180	141	10	4	8
5.50Fx20	7.50-20	6	15	180	141	30	4	8
5.50Fx20	7.50-20	5	19	175	136	25	4	7
5.50Fx20	7.50-20	6	15	180	141	46	4	8
5.50Fx20	7.50-20	6	19	152	117.7	10	8	4
5.50Fx20	7.50-20	6	15	180	141	10	8	4
W7x20	8.3-20	6	17	161	102	65	3.5	8
W7x20	8.3-20	6	17	161	102	5	3.5	8
W7x20	8.3-20	6	15	161	102	50	3.5	8
W7x22	8.3-22	6	14.5	152.4	117.6	21	3.5	8
W7x22	8.3-22	6	15.75	141	95	62.25	3.5	8
W7x24	8.3-24	6	17	161	100	15	3.5	8
W7x24	8.3-24	8	16.5	330	290.5	161.6	4	9
W7x24	8.3-24	6	17	285	250	20	3.5	10
W7x24	8.3-24	8	17.5	203.2	152.4	40	4	10
W7x24	8.3-24	6	17	285	250	123.5	4	8
W7x24	8.3-24	6	17	165	130	54	4	8
W7x24	8.3-24	8	19	203.2	152.6	5	3.5	8
W7x24	8.3-24	6	18	165	130	54	3.5	8
W7x24	8.3-24	6	18	165	130	5	3.5	8
W8x24	9.5-24	6	20	205	161	68.7	4	9
W8x24	9.5-24	8	17	330	290.5	174.3	4	9
W8x24	9.5-24	8	17.5	203.2	152.4	40	4	10
W8x24	9.5-24	8	17	330	290.5	174.3	4	9
W8x24	9.5-24	6	18.8	165	120	1	3.5	8
W10x24	11.2-24	8	17	203.2	151	4	4	8
W10x24	11.2-24	6	18.8	165	120	76	4	8
W10x24	11.2-24	8	17	330	290.5	26	4	9
W10x24	11.2-24	5	17	140	92	10	4	8

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W10x24	11.2-24	6	18.8	165	120	0	4	8
W10x24	11.2-24	8	17	335	290.5	213	4	9
W10x24	11.2-24	8	21	275	221	21	4	9
W10x24	11.2-24	8	17.5	203.2	152.4	31	4	10
W10x24	11.2-24	8	17.5	203.2	152.4	83	4	10
W10x24	11.2-24	8	17	330	290.5	26	4	9
W10x24	11.2-24	8	17	330	290.5	81	4	8
W10x24	11.2-24	8	19	275	221	30.5	4	8
W10x24	11.2-24	8	17	330	290.5	48.5	4	8
W10x24	11.2-24	8	19	275	221	1.5	4	8
W10x24	11.2-24	8	17	330	290.5	30.5	4	8
W10x24	11.2-24	6	17	285	250	42.5	4	8
W10x24	11.2-24	8	17	330	290.5	4	4	8
W10x24	11.2-24	8	19	275	221	26	4	8
W10x24	11.2-24	8	19	203.2	152.6	4	4	8
W10x24	11.2-24	8	19	275	221	4	4	8
W10x24	11.2-24	8	18	165	130	63.5	4	8
W12x24	13.6-24	8	17	330	290.5	26	4	9
W12x24	13.6-24	8	21	275	221	9	4	10
W12x24	13.6-24	8	17	330	290.5	26	4	9
W12x24	13.6-24	8	16.5	330	290	87	4	10
W12x24	13.6-24	8	22	275	221	87	4	10
W12x24	13.6-24	8	17	330	290.5	101	4	8
W12x24	13.6-24	8	17	330	290.5	65	4	12
W12x24	13.6-24	8	18.8	203.2	152.6	24	4	8
W12x24	13.6-24	8	17	330	290.5	4	4	9
W12x24	13.6-24	8	17	330	290.5	55.4	4	9
W12x24	13.6-24	8	17	330	290.5	90.4	4	9

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W12x24	13.6-24	8	17	330	290.5	39	4	9
W12x24	13.6-24	8	18.8	203.2	152.6	26	4	8
W12x24	13.6-24	8	17	330	290.5	39	4	9
W12x24	13.6-24	8	17.2	203.2	152.4	106.4	4.5	10
W13x24	14.9-24	8	18.8	203.2	152.6	26	4	8
W13x24	14.9-24	8	26	190	145	90	4	14
W11x26	12.4-26	8	17	330	290.5	31.5	4.5	8.3
W11x26	12.4-26	8	17	330	290.5	104.7	4.5	9
W11x26	12.4-26	8	17	330	290.5	25	4.5	9
W12x26	13.6-26	10	24	275	221	40	4	10
W13x26	14.9-26	8	17	330	290.5	26	5	9
W13x26	14.9-26	8	17	330	290.5	47	4.5	9
W13x26	14.9-26	8	17	330	290.5	178	4.5	9
W13x26	14.9-26	8	17	330	290.5	43	5	10
W13x26	14.9-26	8	17	330	290.5	21	5	10
W13x26	14.9-26	10	21	335	281.5	21	5	10
W13x26	14.9-26	8	17	330	290.5	26	5	9
W13x26	14.9-26	12	17	535	500	13	5	8
W15x26	16.9-26	10	21	335	105	21	5	10
W10x28	11.2-28	8	17	203.2	151.3	4	4	10
W10x28	11.2-28	6	18.8	165	120	76	4	10
W10x28	11.2-28	6	18.8	165	120	100	4	10
W10x28	11.2-28	8	17	330	290.5	26	4	9
W10x28	11.2-28	8	18.8	203.2	152.4	50	4	8
W10x28	11.2-28	8	21	275	221	16.5	4	9
W10x28	11.2-28	8	18.8	203.2	152.6	4	4	8
W10x28	11.2-28	8	20	203.2	163.5	75	4	8
W10x28	11.2-28	8	17	330	290.5	64.5	4	9

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W10x28	11.2-28	8	20	203.2	163.5	249	4	8
W10x28	11.2-28	10	21	335	281.5	54	4	9
W10x28	11.2-28	8	20	203.2	163.5	6	4	8
W10x28	11.2-28	8	18.8	203.2	152.6	36	4	8
W10x28	11.2-28	10	24	335	281	206	4	10
W11x28	12.4-28	8	17	203.2	151.3	4	4	10
W11x28	12.4-28	8	21	210	140.3	85.5	5	12
W12x28	13.6-28	8	17	203.2	151.3	4	4	10
W12x28	13.6-28	10	24	275	221	40	4	10
W12x28	13.6-28	8	17	330	290.5	102	5	9
W12x28	13.6-28	8	20	203.2	152.4	30	5	10
W13x28	14.9-28	10	23	335	281	30	4	9
W13x28	14.9-28	10	23	335	281	155.1	4	10
W13x28	14.9-28	10	23	335	281	190	5	10
W13x28	14.9-28	8	20	203.2	163.5	190.1	5	10
W13x28	14.9-28	8	17	330	190.5	21.5	5	9
W13x28	14.9-28	8	20	203.2	152.4	30	5	10
W13x28	14.9-28	10	21	335	181.5	21	5	9
W13x28	14.9-28	10	23	335	281	10	10	4.5
W14x28	16.9-28	8	20	203.2	152.4	23.3	5	9
W15x28	16.9-28	10	23	335	281	180	4	10
W15x28	16.9-28	10	23	335	281	31	5	9
W15x28	16.9-28	10	23	335	281	215	5	10
W15x28	16.9-28	10	21	335	281.5	36	5	10
W12x30	13.6-30	8	21	203.2	152.4	149.5	5	10
W12x30	13.6-30	8	21	203.2	152.4	30	5	10
W12x30	13.6-30	8	19	203.2	150.1	20	5	10
W12x30	13.6-30	8	17.5	203.2	152.4	70.5	5	12
W12x30	13.6-30	8	24	250	199	0	4	10
W12x30	13.6-30	8	21.4	203.2	152.6	75	4	10
W12x30	13.6-30	8	21	203.2	152.4	20	5	10

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W12x30	13.6-30	8	32	222.25	145	70	5	10
W14x30	16.9-30	8	19	203.2	150.1	70	5	10
W14x30	16.9-30	8	17.5	203.2	152.4	70.5	5	12
W14x30	16.9-30	8	19	203.2	152.4	58	5	12
W14x30	16.9-30	8	19	203.2	152.4	193.3	5	12
W14x30	16.9-30	8	21.4	203.2	152.6	77	4	10
W14x30	16.9-30	8	21	2056	150	70	5	7
W14x30	16.9-30	8	19	203.2	150.1	70	5	10
W15x30	16.9-30	8	19	203.2	152.4	3.5	5	12
W15x30	16.9-30	10	23	335	281	215.4	5	12
W15x30	16.9-30	8	21.5	203.2	152.4	206.5	5	12
W15x30	16.9-30	8	19	203.2	152.4	165.5	5	12
W15x30	16.9-30	10	23	335	281	13	5	14
W15x30	16.9-30	10	23	335	281	19	5	14
W15x30	16.9-30	10	24	335	281	45	5	14
W15x30	16.9-30	12	26	425	371.5	42	5	14
W15x30	16.9-30	10	24	335	281	13	5	14
W16x30	18.4-30	8	21.5	203.2	152.4	220	5	12
W16x30	18.4-30	8	21.5	203.2	152.4	149.5	5	12
W16x30	18.4-30	8	19	203.2	152.4	58	5	12
W16x30	18.4-30	8	19	203.2	152.4	218.75	5	12
W8x32	9.5-32	6	19	180	141	60	4	10
W8x32	9.5-32	6	19	200	125	25	4	10
W8x32	9.5-32	8	21.5	275	221	15	4	10
W8x32	9.5-32	8	16.5	330	290.5	114.5	4	10
W8x32	9.5-32	8	19	330	290.5	113	4	10
W8x32	9.5-32	10	21.5	335	281.5	40	4	10
W10x32	11.2-32	8	17	203.2	151	4	5	10

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W10x32	11.2-32	8	19	203.2	150.1	20	5	10
W10x32	11.2-32	8	32	222.25	164	30	4	10
W10x32	11.2-32	8	20	203.2	152.4	31	4	9
W10x32	11.2-32	5	19	175	136	18	5	10
W10x32	11.2-32	8	19	330	290.5	68	4	10
W10x32	11.2-32	8	23.5	275	221	45	4	10
W10x32	11.2-32	8	21.5	275	221	53	5	10
W10x32	11.2-32	10	21.5	335	281.5	48	5	10
W10x32	11.2-32	8	20	203.2	152.6	30	5	10
W11x30	12.4-32	8	19.5	203.2	152.6	25.4	5	9
W15x34	16.9-34	8	19	203.2	150.1	70	5	10
W15x34	16.9-34	8	22	275	221	20	5	12
W15x34	16.9-34	8	24	250	199	116	6	4
W15x34	16.9-34	8	21	210	140.3	85.5	5	12
W15x34	16.9-34	8	19	203.2	152.4	57.5	5	12
W15x34	16.9-34	8	19	203.2	152.4	204	5	12
W15x34	16.9-34	8	19	203.2	150.1	70	5	10
W15x34	16.9-34	6	19	410	355	70	5	10
W15x34	16.9-34	8	21	203.2	152.4	23	5	12
W15x34	16.9-34	8	23	280	220.5	23	5	12
W15x34	16.9-34	8	21	275	221.3	20	5	12
W15x34	16.9-34	8	21	203.2	152.4	266.5	5	12
W15x34	16.9-34	8	23	280	220.5	252.5	5	12
W15x34	16.9-34	10	26	335	281.5	77	5	12
W15x34	16.9-34	8	21	203.2	152.4	23	12	
DW15x34	16.9-34	8	19	203.2	152.6	18	5	10
DW15x34	16.9-34	8	21.4	203.2	152.6	75	12	
DW15x34	16.9-34	10	24	335	281.5	314.5	5	12

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W12x30	13.6-30	8	32	222.25	145	70	5	10
W14x30	16.9-30	8	19	203.2	150.1	70	5	10
W14x30	16.9-30	8	17.5	203.2	152.4	70.5	5	12
W14x30	16.9-30	8	19	203.2	152.4	58	5	12
W14x30	16.9-30	8	19	203.2	152.4	193.3	5	12
W14x30	16.9-30	8	21.4	203.2	152.6	77	4	10
W14x30	16.9-30	8	21	2056	150	70	5	7
W14x30	16.9-30	8	19	203.2	150.1	70	5	10
W15x30	16.9-30	8	19	203.2	152.4	3.5	5	12
W15x30	16.9-30	10	23	335	281	215.4	5	12
W15x30	16.9-30	8	21.5	203.2	152.4	206.5	5	12
W15x30	16.9-30	8	19	203.2	152.4	165.5	5	12
W15x30	16.9-30	10	23	335	281	13	5	14
W15x30	16.9-30	10	23	335	281	19	5	14
W15x30	16.9-30	10	24	335	281	45	5	14
W15x30	16.9-30	12	26	425	371.5	42	5	14
W15x30	16.9-30	10	24	335	281	13	5	14
W16x30	18.4-30	8	21.5	203.2	152.4	220	5	12
W16x30	18.4-30	8	21.5	203.2	152.4	149.5	5	12
W16x30	18.4-30	8	19	203.2	152.4	58	5	12
W16x30	18.4-30	8	19	203.2	152.4	218.75	5	12
W8x32	9.5-32	6	19	180	141	60	4	10
W8x32	9.5-32	6	19	200	125	25	4	10
W8x32	9.5-32	8	21.5	275	221	15	4	10
W8x32	9.5-32	8	16.5	330	290.5	114.5	4	10
W8x32	9.5-32	8	19	330	290.5	113	4	10
W8x32	9.5-32	10	21.5	335	281.5	40	4	10
W10x32	11.2-32	8	17	203.2	151	4	5	10

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W10x32	11.2-32	8	19	203.2	150.1	20	5	10
W10x32	11.2-32	8	32	222.25	164	30	4	10
W10x32	11.2-32	8	20	203.2	152.4	31	4	9
W10x32	11.2-32	5	19	175	136	18	5	10
W10x32	11.2-32	8	19	330	290.5	68	4	10
W10x32	11.2-32	8	23.5	275	221	45	4	10
W10x32	11.2-32	8	21.5	275	221	53	5	10
W10x32	11.2-32	10	21.5	335	281.5	48	5	10
W10x32	11.2-32	8	20	203.2	152.6	30	5	10
W11x30	12.4-32	8	19.5	203.2	152.6	25.4	5	9
W15x34	16.9-34	8	19	203.2	150.1	70	5	10
W15x34	16.9-34	8	22	275	221	20	5	12
W15x34	16.9-34	8	24	250	199	116	6	4
W15x34	16.9-34	8	21	210	140.3	85.5	5	12
W15x34	16.9-34	8	19	203.2	152.4	57.5	5	12
W15x34	16.9-34	8	19	203.2	152.4	204	5	12
W15x34	16.9-34	8	19	203.2	150.1	70	5	10
W15x34	16.9-34	6	19	410	355	70	5	10
W15x34	16.9-34	8	21	203.2	152.4	23	5	12
W15x34	16.9-34	8	23	280	220.5	23	5	12
W15x34	16.9-34	8	21	275	221.3	20	5	12
W15x34	16.9-34	8	21	203.2	152.4	266.5	5	12
W15x34	16.9-34	8	23	280	220.5	252.5	5	12
W15x34	16.9-34	10	26	335	281.5	77	5	12
W15x34	16.9-34	8	21	203.2	152.4	23	5	12
DW15x34	16.9-34	8	19	203.2	152.6	18	5	10
DW15x34	16.9-34	8	21.4	203.2	152.6	75	5	12
DW15x34	16.9-34	10	24	335	281.5	314.5	5	12

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W11x36	12.4-36	10	24	335	282	236.7	4	10
W11x36	12.4-36	8	19	203.2	152.4	79	4	12
W10x38	11.2-38	8	17	203.2	152.4	44	4	6
W10x38	11.2-38	10	23	335	282	273	5	12
W10x38	11.2-38	10	26	335	281.5	100	4	12
W10x38	11.2-38	8	21	275	221	112.5	4	10
W10x38	11.2-38	8	21	203.2	140	180	5	12
W10x38	11.2-38	10	22	335	282	82	5	12
W10x38	11.2-38	12	22	426	371	108	5	12
W10x38	11.2-38	8	18	330	292	82	5	12
W10x38	11.2-38	10	22.5	335	282	100	5	12
W10x38	11.2-38	8	18	405	362	52	5	12
W10x38	11.2-38	10	23	335	281	152	5	12
W10x38	11.2-38	10	21.5	335	281	152	5	12
W10x38	11.2-38	8	22	275	220.8	198	5	12
W10x38	11.2-38	10	23	335	282	202	5	12
W10x38	11.2-38	10	22	335	282	108	5	12
W10x38	11.2-38	8	18	405	362	100	5	12
W11x38	12.4-38	8	21	203.2	152.4	16	4	12
W11x38	12.4-38	8	19	203.2	150.1	140	4	12
W11x38	12.4-38	8	20	224	180	98	4	10
W11x38	12.4-38	8	32	275	214	259.8	5	6
W11x38	12.4-38	8	24	250	199	76.5	4	6
W11x38	12.4-38	8	21.4	203.2	152.6	75	4	12
W11x38	12.4-38	8	21	295	240	236	5	10
W11x38	12.4-38	8	19	223	180	33.2	5	10
W11x38	12.4-38	8	21	335	281.5	16	5	12
W11x38	12.4-38	8	23	280	220.5	91.5	4	12
W11x38	12.4-38	8	23	280	220.5	200.5		12
W11x38	12.4-38	8	21.5	203.2	141	30	5	12

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W11x38	12.4-38	8	24	275	221	3	5	12
W12x38	13.6-38	8	19	203.2	150.1	21.2	5	10
W12x38	13.6-38	8	19	203.2	150.1	158	5	10
W12x38	13.6-38	8	21	203.2	152.4	30	5	12
W12x38	13.6-38	8	23	280	220.5	30	5	12
DW12x38	13.6-38	8	20.5	203.2	152.4	29.5	5	10
DW12x38	13.6-38	8	20.5	203.2	152.4	213	5	10
DW12x38	13.6-38	8	20.5	203.2	152.4	69.5	5	12
W14x38	15.5-38	8	21.4	203.2	152.6	75	4	12
W15x38	16.9-38	8	19	203.2	150.1	20	5	12
W15x38	16.9-38	8	23	295	240	96	5	12
W15x38	16.9-38	12	22	404	355	185	5	12
W15x38	16.9-38	8	19	203.2	150.1	120	5	12
W15x38	16.9-38	8	23	280	220.5	169.5	5	12
W15x38	16.9-38	10	26	335	281.5	26	5	12
W15x38	16.9-38	10	26	335	281.5	5.5	5	12
W15x38	16.9-38	10	26	335	281.5	46.5	5	12
W15x38	16.9-38	8	21	203.2	152.4	22	5	12
W15x38	16.9-38	10	26	335	281.5	21	5	12
W15x38	16.9-38	10	26	335	281.5	144	5	12
W15x38	16.9-38	10	26	335	281.5	16	5	12
W15x38	16.9-38	8	21	203.2	152.4	88	5	12
W16x38	18.4-38	8	21	203.2	141	110	5	12
W16x38	18.4-38	8	21	275	221	250	5	12
W16x38	18.4-38	8	23	295	240	96	5	12
DW18x24	21L24	8	24	415	368	45	5	12
DW20x26	23.1-26	8	24	415	368	45	5	12
DW25x26	28LR12	8	24	415	368	45	5	12

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W16x38	18.4-38	10	22	480	421.5	94	5	12
W16x38	18.4-38	10	26	335	281.5	115	5	12
W16x38	18.4-38	8	21	295	240	19	5	12
W16x38	18.4-38	8	21	295	240	173	5	12
W16x38	18.4-38	8	21	275	221	44	6	16
W18x38	20.8-38	10	220+1	480	421.5+0.5	376.5	5	12
W18x38	20.8-38	10	26	335	281	96	5	12
W18x38	20.8-38	10	26	335	281	146	5	12
W18x38	20.8-38	10	26	335	281.5	115	5	12
W18x38	20.8-38	10	26	335	281.5	46.5	5	12
W18x38	20.8-38	10	26	335	281.5	205.5	5	12
W15x42	16.9-42	8	24	275	221	106	6	14
W16x42	18.4-42	8	17.5	203.2	150.1	92.5	5	12
W16x42	18.4-42	10	26	335	281	150	6	14
DW16x42	18.4-42	10	24	335	281.5	38	5	12
DW16x42	18.4-42	10	24	335	281.5	14	5	12
DW16x42	18.4-42	10	24	335	281.5	177	5	12
W18x42	20.8-42	10	23	335	281.5	190.5	6	16
W18x42	20.8-42	10	23	335	281	352	6	18
W18x42	20.8-42	10	26	335	281	167.5	6	18
W18x42	20.8-42	12	26	425	371	284.5	6	16
W18x42	20.8-42					19	6	
W18x42	20.8-42	10	26	335	281	240	6	16
DW20x42	23.1-42	10	23	335	281	310	6	18
DW20x42	23.1-42	12	26	425	371		6	16
W7x48	8.3-48	8	21.5	203.2	152.6	43	5	12
W7x48	8.3-48	10	26	335	281	145	6	14
W7x48	8.3-48	8	21.5	203.2	152.6	165	5	12
W8x48	9.5-48	8	24	250	199	18	5	12
W8x48	9.5-48	8	19	203.2	150.1	130	5	12

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W8x48	9.5-48	8	23	203.2	152.4	190	5	12
W10x48	11.2-48	8	20	203.2	150.5	48	5	12
W10x48	11.2-48	8	23	275	221	150	5	12
W10x48	11.2-48	8	21.5	203.2	152.6	82	5	12
W10x48	11.2-48	10	25	335	281	94	5	12
W10x48	11.2-48	12	23	404	352	21	5	12
W10x48	11.2-48	8	21.5	203.2	152.6	40	5	12
W10x48	11.2-48	10	24	335	281.5	308	5	12
W10x48	11.2-48	10	26	335	281.5	40	5	12
W13x48	14.9-48	10	26	335	282	110	6	12
W13x48	14.9-48	10	24	335	282	83	6	14
W13x48	14.9-48	8	21	295	240	110.4	6	12
W13x48	14.9-48	8	22	275	222	183	6	14
W13x48	14.9-48	10	24	335	282	180	6	14
W13x48	14.9-48	10	26	335	282	133	6	12
W13x48	14.9-48	8	22	275	222	183	6	14
W13x48	14.9-48	10	26	335	282	31	6	14
W13x48	14.9-48	10	22	480	421	245	6	14
W13x48	14.9-48	8	21.5	203.2	152.6	395	5	12
W13x48	14.9-48	10	24	335	282	133	6	14
W13x48	14.9-48	8	20	275	222	110	6	12
W13x48	14.9-48	12	24	814	768	98	6	12
W10x54	11.2-54	8	24	250	199	193	5	12
W10x54	11.2-54	8	19	223	180	123	5	12
W10x54	11.2-54	8	20	275	222		5	12
W10x54	11.2-54	10	24	335	282	133	5	12
W10x54	11.2-54	10	24	335	282	185	5	12
W10x54	11.2-54	8	21	203.2	152.4	20	5	13
W10x54	11.2-54	8	21.5	203.2	152.6	82	5	12
W11x54	12.4-54	10	24	335	282	221.5	5	14

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
4.00Ex15	5.00-15	4	20	152	110	35	3	5
4.00Ex16	6.00-16	5	15.7	141.3	110	5.8	3	5
4.50Ex16	6.50-16	6	20	161	102	66	3.5	6
4.50Ex16	6.50-16	6	20	161	102	26	3.5	6
5.50Fx16	7.50-16	6	20	161	102	60	3.5	6
5.50Fx16	7.50-16	6	17	161	102	27	4	6
5.50Fx20	7.50-20	6	16.7	221.3	171	60	4	8
5.50Fx20	7.50-20	5	17	140	110.5	9.85	4	8
W7x20	8.3-20	6	14.5	161	100.5	25	3.5	8
W7x20	8.3-20	6	15	161	102	50	3.5	8
W7x24	8.3-24	8	17	330	290.5	48.5	4	8
W7x24	8.3-24	6	17	161	100	72	3.5	8
W10x24	11.2-24	6	20	165	120	80.5	3.5	8
W10x24	11.2-24	6	17	165	130	39	4	8
W10x24	11.2-24	8	19	203.2	152.6	46	4	8
W10x24	11.2-24	8	19	275	221	11	4	8
W10x24	11.2-24	6	18.8	165	120	50	4	8
W10x24	11.2-24	6	17	180	140.5	84	5	10
W10x24	11.2-24	6	20	165	120	26	3.5	8
W10x24	11.2-24	6	17	285	250.5	37	4	8
W12x24	13.6-24	8	17	330	290.5	82	4	9
W12x24	13.6-24	8	19	203.2	152.6	41	4	8
W12x24	13.6-24	8	17	330	290.5	39.1	4	8
W12x24	13.6-24	8	16.6	330	290.5	50	4	10
W15x24	16.9-24	8	19	203.2	152.6	10	5	8
W11x26	12.4-26	6	17	205	161	18.8	4	8
W11x26	12.4-26	10	21	335	280.5	32	4	10
W12x26	13.6-26	10	24	335	281	49	4	10
W12x26	13.6-26	8	17	330	290	22	4	10
W13x26	14.9-26	8	17	330	290.5	101	5	9
W10x28	11.2-28	8	17	203.2	152.4	60	4	10

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W10x28	11.2-28	6	18.8	165	120	50	4	10
W10x28	11.2-28	10	24	335	281	49	4	10
W10x28	11.2-28	8	19	203.2	152.6	54	4	8
W11x28	12.4-28	6	17	205	161	12.9	4	8
W12x28	13.6-28	8	17	330	290.5	101	5	9
W13x28	14.9-28	10	21	335	281.5	53	5	9
W13x28	14.9-28	10	23	335	281	31	4	9
W15x28	16.9-28	10	21	335	281.5	32	5	9
DW18x28	20.8-28	12	22	426	371	40	5	12
DW20x28	23.1-28	8	17.5	405	362	35	6	12
W14x30	16.9-30	8	17.5	203.2	152.6	72	4	9
W15x30	16.9-30	8	19	203.2	152.4	25	5	12
W15x30	16.9-30	8	21	203.2	152.4	12	5	10
W15x30	16.9-30	8	19	203.2	152.4	18	5	12
W15x30	16.9-30	8	21	203.2	152.4	37	5	10
W15x30	16.9-30	8	21	295	240	96	5	12
DW15x30	16.9-30	10	24	335	281	13	5	14
DW15x30	16.9-30	10	23	335	281	30	5	10
W16x30	18.4-30	8	21.5	203.2	152.4	0	5	12/6
DW16x30	18.4-30	10	24	335	281	30	5	14
DW16x30	18.4-30	10	24	225	161	49.3	6	14
DW16x30	18.4-30	10	24	225	176	127.3	6	14
DW16x30	18.4-30	8	24	275	221	50	6	16
DW16x30	18.4-30	8	18	405	362.5	12	5	14
DW20x30	23.1-30	8	18	405	362.5	40	6	12
DW20x30	23.1-30	12	□17	590	550	85	7	10
W7x32	8.3-32	9	17.5	241.3	200	30	5	10
DW27x32	30.5-32	15	24	335	281	5	7	16
DW27x32	30.5-32	10	24	335	281	150	7	16
DW27x32	30.5-32	10	24	335	281	134	7	16
W15x34	16.9-34	8	21	203.2	152.4	53	5	12

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W15x34	16.9-34	8	23	280	220.5	27	5	12
W8 x38	11.2-38	8	18	275	221	118	5	12
W10x38	11.2-38	8	21.5	275	221	48	5	12
W10x38	11.2-38	8	18	405	362	18	5	12
W10x38	11.2-38	10	23	335	282	105	5	12
W10x38	11.2-38	10	24	335	281	88	5	12
W10x38	11.2-38	10	24	335	281	54	5	12
W10x38	11.2-38	8	19	250	199	70	5	12
W10x38	11.2-38	8	17.5	330	293	28	5	12
W11x38	12.4-38	8	21.4	203.2	152.4	107.5	5	12
W12x38	13.6-38	8	26	432	350	50	6	16
W12x38	13.6-38	8	20	203.2	152.4	30	5	12
W14x38	16.9-38	8	26	432	350	50	6	16
W15x38	16.9-38	8	21	203.2	152.4	14	5	12
W15x38	16.9-38	8	19	203.2	150.1	32	5	12
W16x38	18.4-38	8	23	280	220.5	5	6	12
W16x38	18.4-38	8	21	295	240	96	5	14
W16x38	18.4-38	10	26	335	281	96	5	12
W18x38	20.8-38	8	23	275	1221	72	5	12
DW20Bx38	23.1-38	8	21	295	240	50	6	16
DW20x38	23.1-38	12	24	814	768	129	6	14
DW20x38	23.1-38	10	23	335	281.5	32	6	16
DW23x38	26L-38	12	24	875	767	24	6	14
DW23x38	26L-38	10	23	335	281.5	6	6	14
DW27Bx38	30.5-38	10	24	335	281	100	7	16
DW18x42	18.4-42	10	23	335	281	352	6	16
DW18x42	18.4-42	10	23	335	281	402	6	16
DW20x42	23.1-42	10	23	335	281.5	57	6	14
DW20x42	23.1-42	10	24	814	768	68	6	12
DW20x42	23.1-42	10	23	335	281	92	6	16
DW25x42	28-42	12	24	814	768	95	7	16

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
DW25x42	28-42	10	23	335	281.5	6.5	6	14
DW13x46	14.9-46	16	□17	787.4	732	21	6	12
DW16x46	18.4-46	16	□17	787.4	732	20	6	12
W10x48	11.2-48	8	21.5	203.2	152.4	74	5	12
W13x48	16.9-48	8	20	275	221	46	6	14
W13x48	16.9-48	8	24	275	222	110	6	14
W10x54	11.2-54	8	17	330	290.5	3.5	5	13
W10x54	11.2-54	8	20	275	221	60	5	14
W10x54	11.2-54	10	24	335	281	180	5	14
W10x54	11.2-54	8	21.5	203.2	152.4	114	5	14
W10x54	11.2-54	8	23	280	223	20	5	13
W8x60	11.2-60	8	19	203.2	152.4	50	5	10



其它系列 Other Series



车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
9.00x15.3	10-15	5	17.5	205	158.5	0	4	6
9.00x15.3	10-15	5	15	140	110	50	4	6
9.00x15.3	10-15	6	21.5	205	153	118.4	4	8
DT14-24	15-24	12	17.5	535	500.5	5	5	
DT14-24	15-24	8	23	240	172/160	8	5	8-6
DT14-24	15-24	8	23	240	160/172	8	5	8-6
DT14-24	15-24	8	23	210	145/160	8	5	8-6
W15x24	16.9-24	8	22	275	221	266	5	12
W15x24	16.9-24	10	24.5	275	221	19	5	12
W8x20	9.5-20	8	16.7	203.2	152.4	54.7	4	5
DW10x20	11.2-20	8	16.5	203.2	152.4	50.8	5	6
DW10x20	11.2-20	9	16.7	203.2	203	71.7	4	6
DW10x20	13.6-20	8	16.5	203.2	152.4	52	4	6
DW10x20	13.6-20	8	16.5	203.2	152.4	36	4	6
W11x16.1	14L-16.1	6	15	152.4	117.6	28.7	5.5	10
W11x16.1	14L-16.1	6	15	152.4	117.6	15	5.5	10
W11x16.1	14L-16.1	6	20	180	140	0	5.5	10
W11x16.1	14L-16.1	8	16.7	203.2	152.4	31.75	5.5	10

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
W11x16.1	14L-16.1	6	15	152.4	118	28.7	5.5	10
W14x16.1	16.5L-16.1	8	16.7	203.2	152.4	38	5.5	10
W14x16.1	16.5L-16.1	8	16.7	203.2	152.4	0	5.5	10
W14x16.1	16.5L-16.1	8	16.7	203.2	152.8	39.8	5.5	10
W14x16.1	16.5L-16.1	8	16.7	203.2	152.4	38.25	5.5	10
W16x16.1	19L-16.1	8	16.7	203.2	152.4	10	5.5	10
W16x16.1	19L-16.1	8	16.7	203.2	152.4	46	5.5	10
DW16Lx30	18.4-30	8	20	275	221	95	5	14
DW16Lx42	18.4-42	10	24	335	281.5	26	6	10
DW18Lx24	20.8-24	8	26	222.25	164	140	6	12
DW18Lx38	20.8-38	10	26	335	281	47	5	12
DW18Lx42	20.8-42	10	26	335	281	57	6	14
DW20Ax30	23.1-30	8	20	275	221	116.5	6	14
DW20Bx42	23.1-42	10	23	340	277	31	6	14
DW20x26	23.1-26	8	20.5	275	221	135	6	16
DW20x26	23.1-26	12	26	404	353	113	6	14



卡车、巴士车轮和工程车轮系列

无内胎车轮 Tubeless wheel



车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
17.5x6.00	215/75R17.5	6	32	222.25	164	118	5	12
17.5x6.00	215/75R17.5	5	29	203.2	146	118	5	12
17.5x6.00	8R17.5	6	20.5	190	141	127	5	12
17.5x6.00	8R17.5	10	32	224	171	113.5	5	12
17.5x6.00	8R17.5	6	20.5	205	146	55	5	12
17.5x6.00	8R17.5	5	32.5	203.2	146	115	5	12
17.5x6.00	8R17.5	5	32.5	203.2	134	115	5	12
17.5x6.00	8R17.5	5	32.5	208	150	115	5	12
17.5x6.00	8R17.5	6	32	222.25	164	135	5	12
17.5x6.00	8R17.5	10	32	224	171	135	5	12
17.5x6.00	8R17.5	6	21	205	161	115	5	12
17.5x6.00	8R17.5	5	20	203.2	146	127	5	12
17.5x6.00		支撑圈 (DEMOUNTABLE)				87	5	12

车轮规格 Wheel size	配用轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
17.5x6.75	215/75R17.5	6	32	222.25	164	140	5	12
17.5x6.75	215/75R17.5	5	29	203.2	146	140	5	12
17.5x6.75	9R17.5	6	20.5	190	141	142	5	12
17.5x6.75	9R17.5	8	26	275	221	143	5	12
17.5x6.75	9.5R17.5	5	32.5	203.2	146	140	5	12
17.5x6.75	9R17.5	5	32.5	203.2	134	140	5	12
17.5x6.75	9R17.5	5	32.5	208	150	140	5	12
17.5x6.75	9.5R17.5	6	32	222.25	164	140	5	12
17.5x6.75	9R17.5	10	32	224	171	140	5	12
17.5x6.75	9R17.5	6	21	205	161	140	5	12
17.5x6.75	9R17.5	5	20	203.2	146	140	5	12
17.5x6.75		支撑圈 (DEMOUNTABLE)				99	5	12
19.5x6.00	8R19.5	6	32	222.25	164	135	5	12
19.5x6.75	9R19.5	6	32.5	222.25	164	140	5	12
19.5x6.75	9R19.5	8	32.5	275	214	140	5	12
19.5x6.75	9R19.5	8	26	275	221	150	6	14
22.5x6.00	8R24.5	8	32.5	275	214	133	6	12
22.5x6.75	9R22.5	8	32	275	214	155	4	12(14)
22.5x6.75	9R22.5	8	32	275	214	152	4	12(14)
22.5x6.75	9R22.5	10	26	285.75	221	169	4	12(14)
22.5x6.75	9R22.5	8	32	275	214	145	4	12(14)
22.5x7.50	10R22.5	10	26	285.75	220	152	6	14
22.5x7.50	10R22.5	8	32	275	214	152	6	14
22.5x7.50	10R22.5	10	32	285.75	221	165	6	14
22.5x7.50	10R22.5	10	26	335	281	165	6	14
22.5x7.50	10R22.5	8	32.5	285	221	60	6	14
22.5x7.50	10R22.5	10	32	285.75	222	165	6	14
22.5x7.50	10R22.5	8	32	275	214	165	6	14
22.5x7.50		支撑圈 (DEMOUNTABLE)				120	6	14
22.5x8.25	11R22.5	8	32	285.75	221	165	6(7)	14
22.5x8.25	11R22.5	10	32	285.75	222	168	6(7)	14

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
22.5x8.25	11R22.5	10	26	335	281	169	6(7)	14
22.5x8.25	11R22.5	10	26	335	281	165	6(7)	14
22.5x8.25	11R22.5	8	32	285	221	165	6(7)	14
22.5x8.25	11R22.5	10	26	285.75	220	168	6(7)	14
22.5x8.25	11R22.5	10	26	335	281	171	6(7)	14
22.5x8.25	11R22.5	10	26	335	281	166	6(7)	14
22.5x8.25	11R22.5	10	32	285.75	222	165	6(7)	14
22.5x8.25	11R22.5	10	26	285.75	220	0	6(7)	14
22.5x8.25	支撑圈 (DEMOUNTABLE)					120	6(7)	14
22.5x8.25	11R22.5	8	32	285.75	221	165	6(7)	14
22.5x8.25	11R22.5	10	32	285.75	222	168	6(7)	14
22.5x8.25	11R22.5	10	26	335	281	169	6(7)	14
22.5x8.25	11R22.5	10	26	335	281	165	6(7)	14
22.5x8.25	11R22.5	8	32	285	221	165	6(7)	14
22.5x8.25	11R22.5	10	26	285.75	220	168	6(7)	14
22.5x8.25	11R22.5	10	26	335	281	171	6(7)	14
22.5x8.25	11R22.5	10	26	335	281	166	6(7)	14
22.5x8.25	11R22.5	10	32	285.75	222	165	6(7)	14
22.5x8.25	11R22.5	10	26	285.75	220	0	6(7)	14
22.5x8.25	支撑圈 (DEMOUNTABLE)					120	6(7)	14
22.5x9.00	12R22.5	8	32	285.75	221	175	6(7)	14
22.5x9.00	12R22.5	10	32	285.75	222	178	6(7)	14
22.5x9.00	12R22.5	10	26	335	281	175	6(7)	14
22.5x9.00	12R22.5	10	27	335	281	175	6(7)	14
22.5x9.00	12R22.5	10	26	335	281	173	6(7)	14
22.5x9.00	12R22.5	8	32	285	221	170	6(7)	14
22.5x9.00	12R22.5	10	26	285.75	220	171	6(7)	14
22.5x9.00	12R22.5	10	26	335	281	174	6(7)	14
22.5x9.00	12R22.5	10	26	335	281	165	6(7)	14
22.5x9.00	12R22.5	10	26	335	281	169	6(7)	14
22.5x9.00	12R22.5	8	32	285	221	176	6(7)	14

车轮规格 Wheel size	配备轮胎 Equipped with tyre	螺栓孔 Bolt hole			中心孔直径 Center hole diameter	偏距 Setover	材料厚度 Material thickness	
		孔数 Hole count	直径 Diameter	分布圆直径 Distribution circle diameter			轮辋 Wheel rim	轮辐 Wheel arm
22.5x9.00	12R22.5	10	32	285.75	222	178	6(7)	14
22.5x9.00	12R22.5	10	26	285.75	220	170	6(7)	14
22.5x9.00	12R22.5	10	26	285	281	0	6(7)	14
22.5x9.00	支撑圈 (DEMOUNTABLE)					130	6(7)	14
22.5x9.75	12R22.5	10	26	335	281	180	6(7)	14(16)
22.5x11.75	15R22.5	10	26	335	281	0	6(7)	14(16)
22.5x11.75	15R22.5	10	26	335	281	120	6(7)	14(16)

工程钢圈 Engineering Steel Rings



车轮规格 Rim size	推荐配备 轮胎 Standard tyre	主要尺寸 mm Component Size MM								重量 Weightkg
		A	B	C	D	E	F	G	H	
20-10.00/1.7	14.00-20	254.0	514.4	43.0	473.0	140.2	51.6	476.4	18.2	54.4
21-10.00/1.7	14.00-21	254.0	533.4	43.0	492.0	140.2	51.6	495.4	18.2	57.3
21-18.00/1.5	24.00-21	475.2	533.4	38.1	492.0	250.8	51.6	495.4	18.2	78.0
21-18.00/1.7	12.00-25	215.9	614.4	43.0	574.0	140.2	51.6	551.0	18.2	66.3
24-10.00/1.7	14.00-24	254.0	614.4	43.0	574.0	140.2	51.6	551.0	18.2	66.3
25-10.00/1.5	14.00-25	254.0	635.0	38.1	593.6	140.2	51.6	597.0	18.2	68.5
25-14.00/1.5	17.50-25	355.6	635.0	38.1	593.6	203.7	51.6	597.0	18.2	82.0
25-17.00/1.7	20.50-25	430.0	635.0	43.0	568.2	228.2	51.6	597.0	18.2	87.0
25-30.00/1.5	67x34.00-25	762.0	635.0	38.1	593.6	394.2	51.6	597.0	18.2	128.0
25-36.00/1.5	66x44.00-25	914.4	635.0	38.1	593.6	470.4	51.6	597.0	18.2	143.0
20-7.5/1.7	10.00-20	190.5	514.4	43.0	469.0	122.0	72.3	443.0	22.2	46.0
20-10.5/1.7	14.00-20	254	514.4	43.0	469.0	143.0	72.3	443.0	22.2	58.0
20-11.25/2.0	16.00-20	286	514.4	51.0	469.0	170.0	72.3	443.0	22.2	67.0
25-17.00/2.0	20.50-25	430.0	635.0	51.0	574.6	273.4	82.7	597.0	26.2	165.0
25-19.50/2.5	23.50-25	495.0	635.0	51.0	574.6	273.4	82.7	597.0	26.2	186.0
25-22.00/3.0	26.50-25	559.0	635.0	76.2	574.6	305.4	82.7	597.0	26.2	215.0
25-24.00/3.0	30-65-25	609.6	635.0	76.2	574.6	330.7	82.7	597.0	26.2	225.0
25-25.00/3.5	29.50-25	635.0	635.0	88.9	574.6	343.4	82.7	597.0	26.2	257.0